

IP видеокамери Cantonk:

H264 / H265/H264+/H265+ Hikvision / XM / ONVIF съвместими

Тези камери имат пълна функционална съвместимост с всички ONVIF устройства.

В режим „HIK ptocol enable“ те са напълно съвместими с H264/H264+ и H264/H264+/H265/H265+ видеорекордерите на Hikvision , както и със софтуера iVMS4200 / iVMS4500, вкл. функцията детекция и запис на движение.

The screenshot shows the 'TCP/IP Port' configuration page. It has two main sections: 'Port' and 'Protocol Port'.
 In the 'Port' section:
 - HTTP Port is set to 8865.
 - RTSP Port is set to 554.
 - HTTPS Port is set to 443.
 In the 'Protocol Port' section:
 - ONVIF Port is set to 8999, with the checkbox 'ONVIF Protocol Enable' checked.
 - HIK Port is set to 8000, with the checkbox 'HIK Protocol Enable' checked.
 - XM Port is set to 34567, with the checkbox 'XM Protocol Enable' unchecked.
 At the bottom, there is a blue 'Save' button.

В режим „XM ptocol enable“ те са напълно съвместими с всички H264 и H265 XM базирани видеорекордери, както и със софтуера CMS3.1xxx, CMS2.0xxx, vMEye_super, XM eye, вкл. функцията детекция и запис на движение.

камера	описание	цена лв с ДДС
 IP-CW60-HHL200 IMX307 + Hi3516EV200	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516E V200, WDR ; Starlight Main Stream: 1080P@25fps; 3MP F1.6 HD Lens, With IR-CUT Plastic & Weatherproof IR Camera IP66 Anti-Cut 3-Axis Metal Bracket Size:162 x 88 x 86(D)mm Weight: 600g IR LED: 42μ x 4PCS IR range: 60M Board Lens : 2,8 , 3,6, 6 mm	165
 IPSL20HL200 IMX307 + Hi3516CV300	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR ; Starlight Main Stream: 3MP@15fps/1080P@30fps; 3MP F1.6 HD Lens, With IR-CUT IR LED: 14μ x 18PCS IR range: 20m Water resistance: IP66, DOME Alum.case, 95 X 76 mm Lens 2.8 / 3,6 / 6 mm 4x AF http://www.cantonk.com/product/NetworkCameras/2MPSeries/FixedLensDome/2017/0803/1921.html	135

IP-PTN60HL200  IMX307 + Hi3516CV300	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR ; Starlight Main Stream: 1080P@30fps; 3MP F1.6 HD Lens, With IR-CUT Plastic & Weatherproof IR Camera IP66 manual zoom lens 6 - 22 mm http://www.cantonk.cn/uploadfile/cantonk/specification%20-%20PDF/Network%20Cameras/2MP%20201706/bullet/IP-PTN60-2MP.pdf	200
 IPTA30HL200 IMX307+Hi3516CV300	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR ; Starlight Main Stream: 1080P@25fps; 3MP F1.6 HD Lens, With IR-CUT Board Lens 2.8 / 3.6 mm/F2.0 IR LED: 42μ x 4 PCS Water resistance: IP66 Alum. case Anti-Cut 3-Axis Bracket Size: 170(W)x75(H)x77(D)mm, Weight: 750g	165
 IPTA30HP200 IMX327+Hi3516CV300	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR ; Super Starlight Main Stream: 1080P@25fps; 3MP F1.6 HD Lens, With IR-CUT Board Lens 2.8 / 3.6 mm IR LED: 42μ x 4 PCS Water resistance: IP66 Alum. case Anti-Cut 3-Axis Bracket Size: 170(W)x75(H)x77(D)mm, Weight: 750g	180
 IPBQ60HS500 IMX335 + Hi3516D 2.7-13.5 mm 5X AF	5 Mp 1/2.8" SONY Starvis Back-illuminated CMOS sensor HISILICON Hi3516D, DWDR; With IR-CUT Including Internal POE Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps; 5MP HD Lens 2.7-13.5mm Motor Zoom Auto Focus Lens	225
 IPCDPHL200 IMX307 + Hi3516CV300	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR; Starlight Main Stream: 1080P@25fps, 3M@15fps; 3MP F1.6 HD Lens, With IR-CUT 2.8 / 3.6 mm Plastic IR Dome Camera IR LED: 14μ x 18PCS 92(W) x 79(H) x 92(D)mm	125

IP ВИДЕОРЕКОРДЕРИ

Номенклатура	характеристика	LAN/Internet access:	цена лв с ДДС
 NVR5116PF XM	16*1080P /16*960P, Hi3536C ,2xHDD, HDMI/VGA/1080p 10/100/1000 MBps LAN 12V/2A power adapter XM software H264/H265	port 34567 vMeye super, CMS3.1.0.8 ONVIF	180
 NVR5132PF XM	32*1080P /32*960P, Hi3536,2xHDD, HDMI/VGA/1080p 10/100/1000 MBps LAN 12V/2A power adapter XM software H264/H265	port 34567 vMeye super, CMS3.1.0.8 ONVIF	260
 DS7608NI-Q1 Hikvision	8x 1080p@30fps 1 x HDD Hikvision software , H264/H265/H264+/H265+ https://www.hikvision.com/europe/Products/Network-Video-Recorder/7600/DS-7608/7616NI-Q1	port 8000 iVms 4200 iVms 4500 ONVIF	216
 DS7616NI-K2 Hikvision	16x 1080p@30fps 2 x HDD Hikvision software , H264/H265/H264+/H265+ https://www.hikvision.com/europe/Products/Network-Video-Recorder/7600/DS-7608/7616NI-K2	port 8000 iVms 4200 iVms 4500 ONVIF	396
 DS7616NI-Q1 Hikvision	16x 1080p@30fps 1 x HDD Hikvision software , H264/H265/H264+/H265+ http://www.sectron.com/bg/product/8456/ds-7616-ni-q1	port 8000 iVms 4200 iVms 4500 ONVIF	255
 DS7716NI-K4 Hikvision	16x 1080p@30fps 4 x HDD Hikvision software , H264/H265/H264+/H265+ https://www.hikvision.com/europe/Products/Network-Video-Recorder/7700/DS-7716/7732NI-K4	port 8000 iVms 4200 iVms 4500 ONVIF	690
 DS7608NI-Q1 Hikvision	4x 1080p@30fps 1 x HDD Hikvision software , H264/H265/H264+/H265+ https://www.hikvision.com/europe/Products/Network-Video-Recorder/7600/DS-7608/7616NI-Q1	port 8000 iVms 4200 iVms 4500 ONVIF	146

други IP камери **H264**

Номенклатура	характеристика	LAN/Internet	лвс ДДС
 JVS-N63-HY	1/4" OmniVision 1.0 Megapixel CMOS Sensor OV9712S, HISILICON DSP Hi3518E Main Stream: 720P@25fps; 12V DC/ 300mA 2 Megapixel HD Lens, with IR-CUT 4mm IR LED: 2PCS Array Lights ,plastic case ext.audio in	port 9101 CLOUDSEE: PC,Android,Iphone Jovision NVR system NETIP , ONVIF	45
 JVS-N73-HY	1/3" Aptina 1.3 Megapixel CMOS Sensor ARO130 HISILICON DSP Hi3518C Main Stream: 960P@25fps; 2 Megapixel HD Lens, with IR-CUT 6mm 12V DC/ 300mA IR LED: 2PCS Array Lights ,plastic case ext.audio in	port 9101 CLOUDSEE: PC,Android,Iphone Jovision NVR system NETIP , ONVIF	70

 JVS-N83-HY	1/2.7" OmniVision 2.0 Megapixel CMOS Sensor OV2710 HISILICON DSP Hi3516C Main Stream: 1080P@25fps; 3 Megapixel HD Lens, with IR-CUT 3.6mm, 6mm 12V DC/ 300mA ext.audio in / video/audio stream IR LED: 2PCS Array Lights ,plastic case ext.audio in	port 9101 CLOUDSEE: PC,Android,Iphone NETIP , ONVIF Jovision NVR system	90
 JVS-N5DL-HC POE	1/2.7" OmniVision 2.0 Megapixel CMOS Sensor OV2710 HISILICON DSP Hi3516C Main Stream: 1080P@25fps; 3 Megapixel HD Lens, with IR-CUT 2.8-12mm POE- 802.3 AF/AT ext.audio in / video/audio stream 24 IR LED metal case ext.audio in / video/audio stream	port 9101 CLOUDSEE: PC,Android,Iphone NETIP , ONVIF Jovision NVR system	120
 JVS-N5DL-HC POE	1/2.7" OmniVision 2.0 Megapixel CMOS Sensor OV2710 HISILICON DSP Hi3516C Main Stream: 1080P@25fps; 3 Megapixel HD Lens, with IR-CUT 3,6 , 6 mm POE- 802.3 AF/AT ext.audio in / video/audio stream 24 IR LED metal case ext.audio in / video/audio stream	port 9101 CLOUDSEE: PC,Android,Iphone NETIP , ONVIF Jovision NVR system	110
 JVS-N4DL-HC POE	1/3" Aptina 1.3 Megapixel CMOS Sensor ARO130 HISILICON DSP Hi3518C Main Stream: 960P@25fps; 2 Megapixel HD Lens, with IR-CUT 3.6mm POE- 802.3 AF/AT 24 IR LED metal case ext.audio in / video/audio stream	port 9101 CLOUDSEE: PC,Android,Iphone NETIP , ONVIF Jovision NVR system	10085
 JVS-N4DL-HG	1/3" Aptina 1.3 Megapixel CMOS Sensor ARO130 HISILICON DSP Hi3518C Main Stream: 960P@25fps; 2 Megapixel HD Lens, with IR-CUT 2.8 mm 12V DC/ 300mA 24 IR LED metal case ext.audio in	port 9101 CLOUDSEE: PC,Android,Iphone NETIP , ONVIF Jovision NVR system	85
 JVS-N81-HY-S POE	1/2.7" OmniVision 2.0 Megapixel CMOS Sensor OV2710 HISILICON DSP Hi3516C Main Stream: 1080P@25fps; 3 Megapixel HD Lens, with IR-CUT 3,6 / 6 POE 802.3 AF/AT ,IR LED: 4PCS Array Lights metal case, with bracket ext.audio in / video/audio stream	port 9101 CLOUDSEE: PC,Android,Iphone Jovision NVR system NETIP , ONVIF	135
 JVS-N71-ZCP	1.3MP IP Camera for Car Plate Recognition 1/3" Aptina 1.3 Megapixel CMOS Sensor ARO130 HISILICON DSP Hi3518C Main Stream: 960P@25fps; 2 Megapixel HD Lens, with IR-CUT 8 mm 12V DC/ 300mA with White LED lamp	port 9101 CLOUDSEE: PC,Android,Iphone Jovision NVR system NETIP , ONVIF	400
 KDM-6716B	H.264 Dual stream encoding;1/3"AR0130 1.3 Megapixel CMOS, : 1280*960@ 25fps,3.7/6mm pinhole lens;Support Multi-Screen software and CMS	ONVIF2.4 CMS3.0 port 34567 CMS3.0.9.xx VmEye super, XMEYE	80

 JVS-H210	1/4" CMOS,with 3.6mm lens 1Mp 720p Hi3518E+OV9712S ★Built-in MIC & speaker and audio ★Day&Night with IR-CUT,10 pcs of Led ★AP&Soundwave Configuration WiFi only ! SD card support - CIF	port 9101 CLOUDSEE: PC,Android,Iphone Jovision NVR system NETIP, ONVIF	36
---	--	---	----

кабели и аксесоари

ВИД	разфасовка	единична цена лв с ДДС /брой, метър/
кабел RG174U , черен	200m	0.39
кабел комбиниран / микрокоакс.+захранване / бял/чер	100м, 200м	0.80
кабел FTP 5E AWG24 Cu , сив , черен	305м	0.55
кабел FTP 5E AWG24 Cu / М , сив , с носещо въже	305м	0.75
кабел FTP 5E AWG24 Cu , черен, сертифициран / по-устойчив на външни условия/	305м	0.65
кабел ШВПС 2x1.0 мм2 бял	100м	0.60
BNC конектор	100	0.70
захр. бокса 2.1мм женска	1	0.50
разклонителна кутия -бяла, IP54 85x85mm , 100x100mm	1	1.30
кутия ABS IP66 200x120x75	1	14
кутия ABS IP66 272x185x75	1	19
обективи CS , C - 2.8,4,6,8,12,16,25,35mm	1	3
обективи CS DC drive 4/6/8/12/16/ 3-8 mm	1	5

ЗАХРАНВАЩИ БЛОКОВЕ

номенклатура	описание	цена лв с ДДС
 ST-C-090-12000600CT	захранващ блок 12V/6A изолиран пластмасов корпус , с кабел 220V - двужилен	36
S350-XX 	S350-12 12V DC / 350W S350-24 24V DC / 350W S350-48 48V DC / 350W http://www.smun.cc/en/Catalogue/350w%2048v%20power%20supply-104.html	60 60 60
 LRS150-48 Meanwell	http://meanwell.bg/files/M2016H1/LRS-150-SPEC.pdf 48VDC / 150W	48
 LRS100-12 Meanwell	12VDC / 100W	40
	адаптер 12V/2A	15
DC-DC converter	35-55V DC - 12 V DC 12W разделен галв. 30-60V DC - 12 V DC 30W разделен	12 36
AC-DC	трансформатор 70V DC / 80W , в метална кутия	50

мрежови комутатори

номенклатура	описание	цена лв с ДДС
 switch 8 port 10/100	switch 8 port 10/100 RTL8398N 5V DC - 16 V DC неуправляем	20
DGS-1100-08	D-Link DGS-1100-08, 8 портов 10/100/1000 Gigabit Smart Switch, управляем 5V DC	72
DGS-1100-16 RACK	D-Link DGS-1100-16, 16 портов 10/100/1000 Gigabit Smart Switch, управляем . 220 V AC	220
DGS-1210-24 RACK	D-Link DGS-1210-24, 24-портов 10/100/1000 Gigabit Smart Switch including 4 Combo 1000BaseT/SFP, управляем 220 V AC	280
DGS-1210-28 RACK	D-Link DGS-1210-248 28-портов 10/100/1000 Gigabit Smart Switch including 4 Combo 1000BaseT/SFP, управляем 220 V AC	330
GO-SW-16G RACK	D-LINK GO-SW-16G, 16 портов, Gigabit неуправляем 12V DC	110